



MAILING ADDRESS:

11762 De Palma Road 1C-308

Corona, Ca 92883

Main Office: (951) 667-6106

www.gailmaterialsinc.com

CUSTOM TOPSOIL WITH PAM

Gail Materials custom topsoil with PAM can be used for various planting conditions, from replacing existing native soils to lightweight soils used in above ground planters. Our custom mix starts with a base of finely screened topsoil blended with good Dakota Peat. Nutrients and minerals are added to provide initial plant growth. A soil aggregating polymer (Linear Poly-Acrylamide, AKA: P.A.M.) is added at the manufacturer's label rate.

Average Bulk Density:

via ASTM E2399 max density index 113lbs. per cubic foot

Base Mix for Custom Soil Mix *(may differ based on client requirements):*

85% Finely Screened Topsoil (less than 15% fine gravel)

15% Dakota Peat

3 oz Poly-Acrylamide (AKA: P.A.M.) per cubic yard

2 lbs. per gypsum per cubic yard

½ lbs. iron sulfate per cubic yard

1 lbs 6-24-24 fertilizer per cubic yard

PLANTING RECOMMENDATIONS:

Always follow project guidelines.

INGREDIENTS *(may differ based on client requirements):*

Topsoil, High Quality Organic Matter, Nutrients, Minerals and PAM